

Thermo Scientific TEOM 1405 Ambient Particulate Monitor

Continuous measurement of
ambient particulate concentrations

The Thermo Scientific™ TEOM® 1405 Ambient Particulate Monitor is the replacement for the successful Thermo Scientific TEOM 1400ab Ambient Particulate Monitor which is the choice of air pollution monitoring networks worldwide for the continuous measurement of particulate mass concentrations.

- U.S. EPA PM-10 Equivalent Monitor (EQPM-1090-079)
- Proprietary TEOM technology
- Touch screen user interface
- Embedded FTP server, ethernet, USB, RS232 and RS485 communications
- Activol flow control



The TEOM® 1405 monitor has become the de facto standard for particulate mass concentration measurements in areas such as Canada, Hong Kong, the United Kingdom and France due to the high data quality, reliability and unparalleled support.

This instrument incorporates our proprietary tapered element oscillating microbalance, a microweighing technology that provides true mass measurements. Using a choice of sample inlets, the hardware can easily be configured to measure PM-10, PM-2.5, PM-1 or TSP concentrations. This single cabinet, network ready unit easily accommodates all site requirements and provides internal data storage and advanced analog and serial data input/output capabilities.

The TEOM 1405 monitor provides a self-referencing, NIST-traceable true mass measurement using our proven high-reliability proprietary TEOM technology.

The system differentiates itself from other PM measurement methods by utilizing a direct mass measurement that is not subject to measurement uncertainties found in surrogate techniques such as beta attenuation, light scattering and pressure drop.



Thermo
SCIENTIFIC

Thermo Scientific TEOM 1405 Ambient Particulate Monitor

Measurement Range	0 to 1,000,000 $\mu\text{g}/\text{m}^3$ (1 g/m^3)
Resolution	0.1 $\mu\text{g}/\text{m}^3$
Precision	$\pm 2.0 \mu\text{g}/\text{m}^3$ (1-hour ave), $\pm 1.0 \mu\text{g}/\text{m}^3$ (24-hour ave)
Accuracy	Mass Measurement: $\pm 0.75\%$
Real-time Mass Conc Average	10 min default, 10 to 3600 sec
Long-Term Averaging	30 min, 1, 8 and 24 hr
Data Output Rate	Every 2 seconds
Operating Range	The temperature of the sampled air may vary between -40 and 60 °C. The TEOM Sensor and Control Units must be weather protected within the range of 2 to 40 °C. An optional Complete Outdoor Enclosure provides complete weather protection.
Standard System Configuration	Menu-driven software for user interaction via 1/4 VGA display with touch screen Connecting and Interface Cables, and Vacuum Pump Consumables for average first year's operation (ambient) RPCOMM and ePort software for local or remote communication
Sample Flow	Activol flow control system uses the mass flow sensors and the measured ambient temperature and pressure to maintain constant volumetric flow rates.
Main Flow Rate:	3 l/min
Bypass Flow Rate:	13.67/min
Data Storage	Internal data logging of user-specified variables; capacity of 500,000 records.
Filter Media	Sample Filter: Pallflex TX40, 13 mm effective diameter
Data Output and Input	ePort software to view and change system operation from PC, touch screen user interface Ethernet with embedded FTP server, USB, RS232, RS485, 8 User-Defined Analog Outputs (0-1 or 0-5 Vdc), 2 User-Defined Contact Closure Alarm Circuits, 4 Averaged Analog Inputs (0-5 Vdc) with user-defined conversion to engineering units
Power Requirements	
Instrument:	100-240 VAC, 440 VA, 47-63 Hz
Pump:	120 VAC/60 Hz: 4.25 A; 240 VAC/50 Hz: 2.25 A
Physical Dimensions	W: 17" (43.2 cm) x D: 19" (48.3 cm) x H: 29.5" (75 cm)
Weight:	38 lbs (18 kg)
Safety/Electrical Designations	CE: EN 61326:1997 + A1:1998 + A2:2001 + A3:2003, EN:61010-1 UL: 61010-1:2004, CSA: C22.2 No. 61010-1:2004, FCC: Part 15 Subpart B, Class B
Approvals and Certifications	U.S. EPA PM-10 Equivalent Monitor EQPM-1090-079

To maintain optimal product performance, you need immediate access to experts worldwide, as well as priority status when your air quality equipment needs repair or replacement. We offer comprehensive, flexible support solutions for all phases of the product life cycle. Through predictable, fixed-cost pricing, our services help protect the return on investment and total cost of ownership of your Thermo Scientific products.

For more information, visit our website at thermoscientific.com/air

© 2012 Thermo Fisher Scientific Inc. All rights reserved. All trademarks are the property of Thermo Fisher Scientific Inc. and its subsidiaries. Specifications, terms and pricing are subject to change. Not all products are available in all countries. Please consult your local sales representative for details.

This product is manufactured in a plant whose quality management system is ISO 9001 certified.

USA
27 Forge Parkway
Franklin, MA 02038
Ph: (866) 282-0430
Fax: (508) 520-1460
customerservice.aqi@thermofisher.com

India
C/327, TTC Industrial Area
MIDC Pawane
New Mumbai 400 705, India
Ph: +91 22 4157 8800
india@thermofisher.com

China
+Units 702-715, 7th Floor
Tower West, Yonghe
Beijing, China 100007
+86 10 84193588
info.eid.china@thermofisher.com

Europe
Takkebijsters 1
Breda Netherlands 4801EB
+31 765795641
info.aq.breda@thermofisher.com

Thermo
SCIENTIFIC

Part of Thermo Fisher Scientific